

PRODUCT INFORMATION

SENOSON® A50 EG SOFTFEEL

Characteristics

High impact resistant multi-layer ABS sheet with customized ASA top mayer. Surface is available in Matt or gloss, smooth or embossing. UV stabilized.

Advantages

- Co-extruded, in-line coloured ABS/ASA multi-layer sheets
- Glossy or matt, if required with an embossed ASA surface
- Good UV stability
- Excellent chemical resistance
- Standard colours, special colours on request

Product details

CO-EX ABS/ASA **senosan®** AS50/55 EG
 CO-EX ABS/ASA **senosan®** AS50/55U EG
 U=UV
 Thickness: 2.0 to 8.0 mm
 Width: up to 2,500 mm
 (special formats and thicknesses on request)
 Surface: smooth/embossed
 Colour: on request
 *Embossings: **All embossings**
 (other embossings on request)

Technical properties

Property	Value
Density	see technical data sheet
E-Modul	see technical data sheet
Flexural strength	see technical data sheet
Charpy (ISO 179/1 epA)	see technical data sheet
Approved for	ISO 27956 applications

Minimum quantity 3 t

per thickness: 1 t
 per colour: 3 t
 per embossing: 3 t

Price on request; smaller quantities only possible in case of co-production.

Possible applications

Various parts, e.g. exterior and interior applications

* Embossings: 006RR, 021RN, 003FN, 022HT, 026MW, 016LI, 019SC

Plastic Materials and Processes (NZ) Ltd
 13 John Glenn Avenue
 Albany 0632
 PO BOX 300 - 703
 Albany 0752
 New Zealand



Phone +64 9 414 1600
 Fax +64 9 415 0069
 info@pmpnewzealand.co.nz

Plastic Materials and Processes (Australia) Pty Ltd
 13 Goodyear Drive
 Thomastown,
 Victoria 3074,
 Australia

Phone +61 3 9464 4822
 Fax +61 3 9464 4677
 sales@pmpaustralia.com.au